

PRODUCT DATASHEET

SST CLAS A 60 FIL 7 W/2700K E27

LED RELAX and ACTIVE CLASSIC A | LED lamps, classic bulb shape



AREAS OF APPLICATION

- Supports the bio rhythm when used in bed and children's room
- Outdoor use in outdoor luminaires only (minimum IP65)

PRODUCT BENEFITS

- Creates individual atmospheres: Warm White to relax, Cool White for activity
- Easy change of color temperature with double click of wall switch
- Always fitting light due to two light colors in one lamp: Warm White and Cool White
- Supports the biorhythm through activating and relaxing light color
- Long lifetime of up to 15,000 h
- Low energy consumption
- Easy relamping thanks to compact design
- Makes rooms multi-purpose with adjustable light atmosphere
- Turns kitchens, living rooms or home offices into either a work place or relax area

PRODUCT FEATURES

- Provides color temperatures of 2,700 K and 4,000 K in the same lamp
- Controllable via standard wall switch
- Good quality of light; color rendering index $R_a \geq 80$



- Mercury-free lamps

TECHNICAL DATA


Electrical data

Rated wattage	7.00 W
Nominal wattage	7.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	505
Max. lamp no. on circuit break. 16 A (B)	808
Operating frequency	50...60 Hz

Photometrical data

Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White...Cool White
Color temperature	2700 K
Luminous flux	806 lm
Color rendering index Ra	≥80
Nominal luminous flux	806 lm
Rated color temperature	2700 K

Dimensions & weight



Overall length	105.0 mm
----------------	----------

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	55 °C

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h

Number of switching cycles	100000
-----------------------------------	--------

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Energy efficiency class	A++
--------------------------------	-----

Country-specific categorizations

Order reference	LEDSCLA60ACT/RE
------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075114180	Blister 1	61 mm x 140 mm x 120 mm	55.00 g	1.02 dm ³
4058075114197	Shipping carton box 6	381 mm x 153 mm x 136 mm	474.00 g	7.93 dm ³
4058075434820	Folding carton box 1	60 mm x 60 mm x 145 mm	48.00 g	0.52 dm ³
4058075434837	Shipping carton box 4	139 mm x 134 mm x 120 mm	260.00 g	2.24 dm ³
4058075445352	Shipping carton box 32	- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.